

MT086 One First Tile

Brand	Mohawk Group
Product Type	Tile
DESIGN	
Minimum Sq. Yd.	No minimum
Construction	Tufted
Surface Texture	Textured Patterned Loop
Gauge	1/12 (47.00 rows per 10 cm)
Density	6546
Weight Density	157,104
Stitches Per Inch	9.0 (35.43 per 10 cm)
Finished Pile Thickness	.132" (3.35 mm)
Dye Method	Solution Dyed
Backing Material	EcoFlex ICT
Alternate Backing	Upgrade to NXT or NXT AIR Backing for Red List Free. Min req'd. Contact Rep for Details.
Fiber Type	Colorstrand® SD Nylon
Face Weight	24.0 oz. per sq. yd. (814 g/m2)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Soil Release Technology	Sentry Plus
GSA Stain Release Rating	Pass
Installation Method	Multi-Directional, Monolithic, Quarter Turn
Foot Traffic Recommendation TARR	Severe

SUSTAINABILITY

Pre-Consumer Recycled Content	48 %
NSF 140	Gold
Indoor Air Quality	Green Label Plus 1098
Declare Label	Declared

PERFORMANCE

Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450

SERVICE

Warranties	Lifetime Limited Tile Warranty Lifetime Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants 10 Year Stain Warranty Lifetime Static
------------	---



Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations, or other factors. The performance is not affected by such variances. All Specifications are subject to normal manufacturing tolerances.

www.mohawkgroup.com  
800.554.6637