

BT212 X-Factor Tile

Brand **Mohawk Group**
Product Type **Tile**



DESIGN

Minimum Sq. Yd.	No minimum
Construction	Tufted
Surface Texture	Level Patterned Loop
Gauge	1/10 (39.37 rows per 10 cm)
Density	4037
Weight Density	48,449
Stitches Per Inch	8.0 (31.50 per 10 cm)
Finished Pile Thickness	.107" (2.72 mm)
Dye Method	Solution Dyed
Backing Material	EcoFlex ICT
Alternate Backing	Upgrade to NXT or NXT AIR Backing for Red List Free. Min req'd. Contact Rep for Details.
Fiber Type	Colorstrand® SD Nylon
Face Weight	12.0 oz. per sq. yd. (407 g/m ²)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Soil Release Technology	Sentry Plus
Installation Method	Brick Ashlar, Quarter Turn
Foot Traffic Recommendation TARR	Severe



SUSTAINABILITY

Pre-Consumer Recycled Content	48 %
NSF 140	Gold
Indoor Air Quality	Green Label Plus 1098
Declare Label	Declared



PERFORMANCE

Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450



SERVICE

Warranties	Lifetime Limited Tile Warranty Lifetime Limited Colorfastness to Light 10 Year Limited Colorfastness to Atmospheric Contaminants 10 Year Stain Warranty Lifetime Static
------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------



Color may vary from dye lot to dye lot. Substitution of material may be made due to improved technology, supply limitations, or other factors. The performance is not affected by such variances. All Specifications are subject to normal manufacturing tolerances.

www.mohawkgroup.com
800.554.6637