



CONTESSE

PRODUCT TECHNICAL SPECIFICATION SHEET

| | |
|-----------------------------------|-------------------------|
| Product Name | Pasteur |
| Construction | Multi-Level Loop |
| Dimension | 50 x 50 cm |
| Pile Composition | 100 % Olefin |
| Dye Method | Solution Dyed |
| Gauge | 1/12" |
| Backing Type | E-Bac with fiberglass |
| Pile Weight | 680 gr/m ² |
| Total Weight | 3380 gr/m ² |
| Pile Thickness | 4 mm |
| Total Thickness | 6 mm |
| Tufts per m ² | 186000 |
| Pattern Repeat | 60,96 x 60,96 cm |
| Number of Tiles per Carton | 20 pieces |
| M ² per Carton | 5m ² |
| Flammability - Radiant Panel | ASTM E 648 Class II |
| Flammability - Methenamine Pill | ASTM D2589 Rating 8 |
| Flammability - Smoke Density | ASTM E 662 ≤ 450 |
| Stability - Delamination | ASTM D3936 ≥ 3.0 lbc/in |
| Stability - Dimensional Stability | AACHEN ≤ 0.2 % |
| Stability - Tuft Bind | ASTM D1335 ≥ 8.0 lbs |
| Static Propensity | AATCC 134 ≤ 3.5kV |
| Colour Fastness to Light | AATCC 16 E Rating 4-5 |
| Colour Fastness to Rubbing | AATCC 165 Rating 4-5 |
| Sound Absorption Coefficient | EN ISO 354 0.15 Class E |
| Impact Sound Transmission | EN ISO 140-3 23dB |
| Indoor Air Quality | GLP 6331/6330 |