

PIZARRO


Simple yet brilliant, Pizarro comes together with 12 natural and vibrant colors that allow for all sorts of combinations. While Pizarro can be mixed matched with most other ranges, it can also be blended in itself to create colorful combinations, borders and even color pools. It is designed and manufactured to withstand the toughest conditions and uphold the highest standards to match your expectations.




PIZARRO 2541



PIZARRO 2570




PIZARRO 2574



PIZARRO 2582



PIZARRO 2594




PIZARRO 2573




PIZARRO 2583



PIZARRO 2575




PIZARRO 2576



PIZARRO 2520



PIZARRO 2578



PIZARRO 2577

TECHNICAL SPECIFICATIONS

NORM	TEST	PIZARRO
Construction		Tufted 1/10" Loop Pile
Pile Material		100% PA Solution Dyed
Secondary Backing		Bithumen
Secondary Backing (Optional)		Acoustic Comfort
Size		50 x 50 cm
Packaging		5 m2 per box
Total Weight		4100 g/m2
Pile Weight		540 g/m2
Total Height		5.0 mm
Pile Height		3.0 mm
Tufts/m2		189.600 /m2
Use Classification		Class 33
Castor Chair Test	EN 985	A - Intensive Use
Abrasion	EN 1963	Pass
Vetterman Test	EN1471	Pass
Dimensional Stability	EN 986	Pass
Thermal Isolation	ISO 8302	0.0805 m2 K/W
Sound Absorbtion	ISO 140-8	24 dB
Luxury Class		LC1
Static Loading		Anti-Static
Walk on Test	EN 1815	- 0.1 kV
Horizontal Electrical Resistance	ISO 10965	3 x 10 ⁸ Ohm
Vertical Electrical Resistance	ISO 10965	4 x 10 ¹⁰ Ohm
Reaction to Fire	EN ISO 9239-1	Bfl-s1
Vertical Resistance	BS 4790	Low Radius
Color Fastness to Light	ISO 105 B02	> 5.0
Color Fastness to Rubbing	ISO 105 X12	5.0

